

Obduramus Circum Schacht

Artikel- nummer	DN	Manschetten Länge	Gesamt Ø gerollt	Edelstahlmanschette V4A			EPDM Gummimanschette			Geeignet für Rohre:		. Abdicht- bereich
				Blech- stärke	Rollmaß	max. Auf- spannung	Gummi- stärke	Dicht- noppen- höhe	Höhe inkl. Noppen	Innen Ø min.	Innen Ø max.	
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
P-150-EPDM- 2S-200	150	200	129	1,0	117	154	2,0	5,0	7,0	140	162	110
P-200-EPDM- 2S-200	200	200	164	1,2	150	204	2,0	5,0	7,0	175	215	110
P-250-EPDM- 2S-200	250	200	202	1,2	190	254	2,0	5,0	7,0	215	262	110
P-300-EPDM- 2S-200	300	200	251	1,2	235	306	2,0	6,0	8,0	262	316	110
P-400-EPDM- 2S-200	400	200	345	1,5	325	407	2,0	8,0	10,0	355	420	110
P-450-EPDM- 2S-200	450	200	382	1,5	360	460	2,5	8,0	11,0	400	468	110
P-500-EPDM- 2S-200	500	200	442	1,5	420	506	2,5	8,0	11,0	451	520	110
P-600-EPDM- 2S-200	600	200	531	2,0	510	610	2,5	8,0	11,0	541	623	110
P-700-EPDM- 2S-200	700	200	621	2,0	600	714	2,5	8,0	11,0	631	727	110
P-800-EPDM- 2S-200	800	200	721	2,0	700	810	2,5	8,0	11,0	731	823	110

Maße im Rahmen unserer Fertigungstoleranz.

Obduramus Circum Manhole

Item number	DN	Sleeve length	Total Ø rolled	V4A stainless steel sleeve			EPDM seal			Designed for pipes:		
				Sheet thickness	Roll size	Max. expansion	Rubber thickness	DSealing knob height	Height incl. knobs	Min. internal Ø	Max. internal Ø	Individual Sealing length
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
P-150-EPDM-2S-200	150	200	129	1,0	117	154	2,0	5,0	7,0	140	162	110
P-200-EPDM-2S-200	200	200	164	1,2	150	204	2,0	5,0	7,0	175	215	110
P-250-EPDM-2S-200	250	200	202	1,2	190	254	2,0	5,0	7,0	215	262	110
P-300-EPDM-2S-200	300	200	251	1,2	235	306	2,0	6,0	8,0	262	316	110
P-400-EPDM-2S-200	400	200	345	1,5	325	407	2,0	8,0	10,0	355	420	110
P-450-EPDM-2S-200	450	200	382	1,5	360	460	2,5	8,0	11,0	400	468	110
P-500-EPDM-2S-200	500	200	442	1,5	420	506	2,5	8,0	11,0	451	520	110
P-600-EPDM-2S-200	600	200	531	2,0	510	610	2,5	8,0	11,0	541	623	110
P-700-EPDM-2S-200	700	200	621	2,0	600	714	2,5	8,0	11,0	631	727	110
P-800-EPDM-2S-200	800	200	721	2,0	700	810	2,5	8,0	11,0	731	823	110

Dimensions within the scope of our production tolerances